S9934-LTE OUT



© 2026 Ricon

RICON S9934-LTE-OUT, is an industrial router with LTE Cat.4 support, designed to provide reliable cellular connectivity in harsh outdoor conditions. Its robust IP65 housing and wide operating temperature range of -30 °C to +70 °C make it suitable for use in rain, dust and changing weather conditions. With PoE-enabled Fast Ethernet LAN/WAN ports and a dual SIM slot, it offers flexible connectivity and installation options for outdoor devices.

S9934-LTE-OUT supports network continuity with automatic backup between WAN, WLAN and LTE connections. Thanks to its design suited to pole, panel and cabinet mounting, it is an ideal connectivity solution for IP camera systems, smart city infrastructure, traffic management, outdoor lighting and remote energy monitoring applications.

S9934-LTE-OUT can be configured via the web interface and CLI; it can be monitored centrally and managed remotely through the Ricon Management System (RMS). With SMS-based Zero-Touch provisioning support, it simplifies commissioning especially at hard-to-reach outdoor locations and helps reduce field operation costs and travel time.

Features

- LTE / 4G / 3G support
- Dual SIM / Multi-SIM
- Failover/Failback
- IPSec VPN
- OpenVPN
- L2TP / PPTP
- GRE Tunneling
- DMVPN
- Firewall
- MAC / IP Filter
- DoS/DDoS Protection
- HTTPS / SSH Connection
- Static & Dynamic Routing
- BGP
- OSPF / RIP
- VLAN
- NAT / Port Forwarding / DMZ
- DHCP Server / Client
- Bridging / Passthrough
- Policy-based Routing (PBR)
- Web GUI (HTTPS)
- CLI (SSH / Telnet)
- SNMP
- TR-069
- Syslog / Event Log
- OTA Software Update
- SMS Commands
- Cloud Management Platform
- Wi-Fi 4
- WPA2
- MAC Filter
- Connection timers
- Ping / Uptime Watchdog
- Automation via SMS
- Task definition via script file
- MQTT over TLS
- Identity-Based Firewall
- Cloud Access Control (CASB)
- TLS Inspection

Specifications

Dimensions and Weight

- Height: 75mm
- Width: 60mm
- Depth: 28mm
- Weight: 190g
- Rugged industrial aluminum metal housing
- IP65 protection

Environmental

- Operating Environment Temperature : -30ºC~+70ºC
- Storage Temp. : -40ºC~+85ºC
- Humidity <95%

Certifications

- **ATEX Zone 1 & 21 Certified II 2G Ex db IIB T6 Gb / II 2D Ex tb IIIC T85°C Db**

© 2026 Ricon

General Specs

CPU	MT7628AN
Memory	128MB
HW Watchdog	Connection timers Ping / Uptime Watchdog SMS automation Script tasks
SPI Flash	16MB

Interfaces and Configuration

LAN	1 x 10/100BaseT PoE
WAN	1 x 10/100BaseT PoE
DHCP Server	DHCP Server/Client/Relay, DNS

Cellular Features

Cellular Modem Module	EC200A-EU
Module Type	PCIE
Region	Global
Chipset	UNISOC 8910DM
Category	LTE: Cat.4
Cellular Bands	LTE-FDD B1/ 3/ 5/ 7/ 8/ 20/ 28 LTE-TDD B38/ 40/ 41 WCDMA B1/ 5/ 8 GSM 900/1800 MHz
SIM Support	2 x U-SIM Cards

© 2026 Ricon

Security Features

Firewall	Identity-Based Firewall Cloud Access Control (CASB) TLS Inspection
Filters	Access restriction Wireless access restriction
Misc	Security log Security alarms Packet capture log (pcap to dump file)

Management Features

Management Interfaces	Web GUI (HTTPS) CLI (SSH / Telnet) SNMP TR-069 Syslog / Event Log OTA Firmware Update SMS Command Cloud Management Platform
Version Management	Image Checksum Active version and backup version Automatic rollback when remote upgrade fails
Account Management	Integrated Admin/Guest Accounting TACACS/TACACS+, Radius Auth. models
Retrievable Parameters WEB UI / CLI / TR-069 / SNMP	CLI command-line access SNMP remote monitoring and management Web-based graphical interface management

Cellular Modem Features

APN Data Services	Dynamic APN support SIM PIN management Bridge Mode Support
Modem Interface Configuration	Full band scan Modem Band Lock Automatic/On-demand dialing Enable/Disable Radio Pppd and DHCP dialing options
Modem Backup	Supports backup on interface failure. Supports backup on traffic flow interruptions. Supports automatic connection establishment.

© 2026 Ricon

Wi-Fi	
Chipset	MT7628AN
Wi-Fi Features	Wi-Fi Radio : 1x1 MIMO / 20/40 MHz Frequency Band : 2.4 GHz only Client Capacity : Up to 20~25 simultaneous clients (depends on hardware/device) Wi-Fi Standard (2.4 GHz) : IEEE 802.11 b/g/n MIMO Configuration : 1x1 Channel Bandwidth : 20/40 MHz Modulation : BPSK, QPSK, 16-QAM, 64-QAM Tx Output Frequency Range : 2400–2483.5 MHz Maximum Data Rate : ~150 Mbps (with 40 MHz channel) Security Protocols : WEP, WPA, WPA2 (AES/TKIP) Total Wi-Fi Throughput : Up to ~150 Mbps (ideal conditions, 802.11n, 40 MHz)
Region	Global
Wireless Security	Protocols: WEP, WPA, WPA2 Encryption: AES, TKIP
Mode	Access Point and WiFi Client (Station) modes are supported.

© 2026 Ricon

Network Features

Routing	Static Routing, Dynamic Routing BGP OSPF / RIP VLAN NAT / Port Forwarding / DMZ DHCP Server / Client Bridging / Passthrough Policy-Based Routing (PBR) Support
Tunnels	IPSec VPN OpenVPN L2TP PPTP SSTP GRE Tunneling DMVPN Firewall MAC / IP Filtering DoS/DDoS Protection HTTPS / SSH Access
Routing	NAT Support Port Forwarding DMZ Support
Load Balancing	Per-Packet Routing Support

Ordering Information and Accessories

S9934-LTE OUT	CAT4 Cellular Radio Interface 1xPoE LAN, 1xPoE WAN Fast Ethernet, 2xSIM Slots 2.4GHz Wi-Fi 802.11b/g/n

Defaults

Default Box Contents	1 x S9934-LTE OUT Router Hardware 1 x 3M Antenna for 4G 1 x WiFi antenna for 2.4GHz 1 x 1m. CAT6 Ethernet patch cable

© 2026 Ricon

About Ricon

Ricon is a B2B technology company developing network technologies for the secure, uninterrupted and sustainable communication needs of businesses. With industry experience and a technology-driven approach, it delivers connectivity, communication and management solutions for mobile, fixed and cloud networks.

Helping service providers, businesses and partners build reliable and scalable network infrastructures, Ricon supports the development of strong and sustainable communication infrastructures with solutions that adapt to changing digital needs and requirements.

© 2026 Ricon

Ricon Canada Office (HQ)	Ricon Turkey Office	Ricon Turkey Office ITU	Ricon Italy Office
5063 North Service Road Burlington Ontario L7L 5H6 Canada riconrequest@riconmobile.com +1 (905) 921-3122 +1 (905) 336-2450	Ahi Evran Cad. No: 21 Polaris Plaza Kat: 6-8 Maslak İstanbul riconturkiye@riconmobile.com +90 212 346 26 00	Reşitpaşa Mah. ITU ARI 3 Teknokent No:4-Z101 Sarıyer İstanbul riconturkiye@riconmobile.com +90 212 346 26 00	Via Gaetano Negri 8 20123 Milano Italy riconitaly@riconmobile.com +39 02 87177914