

## S9922M44-LTE



**RICON S9922M44-LTE Router** by Ricon Mobile Inc. Industrial grade quality, designed and manufactured in accordance with 3G/LTE cellular network technology. With embedded cellular module, ATM connection, remote office security connection, data collection etc. It is widely used in many cases such as.

**Ricon Mobile S9922M44-LTE Router** provides maximum service to customers while Zero touch-SMS installation minimizes the need for field service with easy and automatic product installation service. S9922M44 Router, Single Module Single SIM hardware type. The best throughput value of the S9922M44 Router is 200 Mbps.

**Mobile S9922M44-LTE Routers** are web-based and easily routed through CLI. In addition, the Ricon Management System (RMS) successfully accomplishes the goal of reducing the maintenance costs with the ability to access all the Ricon products in the network and to access instant and statistical data on the web environment and manage them 100%.

## Features

- LTE / 4G / 3G support
- Dual SIM / Multi-SIM
- Failover/Failback
- IPSec VPN
- OpenVPN
- L2TP / PPTP
- GRE Tunneling
- DMVPN
- Firewall
- MAC / IP Filtering
- DoS/DDoS Protection
- HTTPS / SSH Access
- Static & Dynamic Routing
- BGP
- OSPF / RIP
- VLAN
- NAT / Port Forwarding / DMZ
- DHCP Server / Client
- Bridging / Passthrough
- Policy-based Routing (PBR)
- Web GUI (HTTPS)
- CLI (SSH / Telnet)
- SNMP
- Syslog / Event Log
- OTA Firmware Update
- SMS Command
- Cloud Management Platform
- Wi-Fi 4
- WPA2
- MAC Filtering
- Connection timers
- Ping / Uptime Watchdog
- Automation with SMS
- Task definition with script
- Modbus TCP / MQTT
- MQTT over TLS
- Identity-Based Firewall
- Cloud Access Control (CASB)
- TLS Inspection

## Technical specifications

### Dimensions and weight

- Height: 178mm
- Width: 105mm
- Depth: 28mm
- Weight: 464gr
- Industrial aluminum metal body

### Environmental

- Idle: 80mA + 12VDC
- Single Module Power Consumption: <5W
- Power Supply: 5 - 35VDC

## General specifications

CPU	MT7628AN
Memory	128MB
HW Watchdog	Connection schedulers Ping / Uptime Watchdog SMS automation Scripting tasks
SPI Flash	16MB

## Interfaces and Configuration

LAN	4 x 10/100TBase Ethernet
WAN	1x10/100 Mb
DHCP Server	DHCP Server/Client/Relay, DNS

## Cellular Specifications

Cellular Modem Module	EC200A-EU
Module Type	PCIE
Region	Global
Chipset	UNISOC 8910DM
Category	LTE: Cat.4
Cellular Bands (SDX62)	LTE-FDD B1/ 3/ 5/ 7/ 8/ 20/ 28 LTE-TDD B38/ 40/ 41 WCDMA B1/ 5/ 8 GSM 900/1800 MHz
SIM Support	2 x U-SIM Cards

## Security Features

Firewall	Identity-Based Firewall Cloud Access Control (CASB) TLS Inspection
Filters	Access restriction Restricting wireless access
Misc	Security logging Security alarms Packet capture logging (Dump to file pcap)

## GNSS / GPS Features (Optional)

Chipset	ATGM336D
Supported Bands	GPS/ QZSS: L1 C/A, L5 GLONASS: L1 Galileo: E1, E5a BDS: B1I, B2a
Default Constellations	GPS + GLONASS + Galileo + BDS + QZSS
Number of Concurrent GNSS	4 + QZSS
Protocols	OSPF Routing protocols RIP Routing protocols WPA2 Wi-Fi encryption protocols Industrial data communication protocols
SBAS	WAAS, EGNOS, MSAS and GAGAN

## Management Features

Management Interfaces	Web GUI (HTTPS) CLI (SSH / Telnet) SNMP Syslog / Event Log OTA Firmware Update SMS Command Cloud Management Platform
Version Management	Image Checksum Active version and backup version Auto rollback feature when remote upgrade fails
Accounts Management	Integrated Admin/Guest accounting TACACS/TACACS+, Radius Auth. models
Retrievable Parameters WEB UI / CLI / TR-069 / SNMP	CLI Command-line access SNMP Remote monitoring and management Web-based graphical interface management

## Cellular Modem Features

APN Data Services	Dynamic APN support SIM PIN management Bridge Mode Support
Modem Interface Configuration	SIM Slot selection Full band-scan Modem Band-Lock Auto/On-Demand dial Enable/Disable Radio Pppd and DHCP dialing options
Modem Failover	Support fail-over on interface drop. Support fail-over on traffic flow interruptions Support Automatic connection recovery.

## Wi-Fi

Chipset	MT7628AN
Wi-Fi Specifications	Wi-Fi Radio : 1x1 MIMO / 20/40 MHz Frequency Band : 2.4 GHz only Client Capacity : Up to ~32 concurrent clients (depends on firmware/device) Wi-Fi Standard (2.4 GHz) : IEEE 802.11 b/g/n MIMO Configuration : 1x1 Channel Bandwidth : 20/40 MHz Modulation : BPSK, QPSK, 16-QAM, 64-QAM Tx Output Frequency Range : 2400–2483.5 MHz Maximum Data Rate : Up to 150 Mbps (with 40 MHz channel) Security Protocols : WEP, WPA, WPA2 (AES/TKIP) Total Wi-Fi Throughput : Up to ~150 Mbps (ideal conditions, 802.11n, 40 MHz)
Region	Global
Wireless Security	Protocols: WEP, WPA, WPA2  Encryption: AES, TKIP
Mode	Accesspoint, WiFi Client (Station) modes supported **MU-MIMO is supported with both modes above **2x2 DL MIMO is supported with both modes above

## Networking Features

Routing	Static Routing ,Dynamic Routing BGP OSPF / RIP VLAN NAT / Port Forwarding / DMZ DHCP Server / Client Bridging / Passthrough Policy-based Routing (PBR)
---------	---

Tunnels	IPSec VPN OpenVPN L2TP PPTP SSTP GRE Tunneling DMVPN Firewall MAC / IP Filtering DoS/DDoS Protection HTTPS / SSH Access
---------	---

Forwarding	NAT Support Port Forwarding DMZ Support
------------	---


Load Balancing	Per-Package Forwarding Support
----------------	--------------------------------

## Ordering Information & Accessories

S9922M44-LTE	CAT4 Cellular Radio Interface 4xLAN, 1xWAN Fast Ethernet, 2xSIM Slots 2.4GHz Wi-fi 802.11b/g/n
--------------	--

## Defaults

Default Box Contents	1 x S9922M44-LTE Router Hardware 2 x 3M Antennas for 4G 1 x WiFi antenna for 2.4GHz and 5GHz 1 x 1m. CAT6 Ethernet patch cable 2 x Mounting kit 1 x 12VDC 1.5A 18W Power Supply
----------------------	--





## About Ricon

At Ricon, we create technology that brings the communication handy.

As a 22 years B2B technology innovation company, we are designing networks that sense, think and act across mobile, fixed and cloud networks.

Service providers, enterprises and partners worldwide trust Ricon to deliver secure, reliable and sustainable networks today – and work with us to create the digital services and applications of the future.

© 2025 Ricon

<b>Ricon Canada Office (HQ)</b> 5063 North Service Road Burlington Ontario L7L 5H6  Canada  <a href="mailto:riconrequest@riconmobile.com">riconrequest@riconmobile.com</a> +1 (905) 921-3122 +1 (905) 336-2450	<b>Ricon Turkey Office</b> Ahi Evran Cad. No: 21 Polaris Plaza Kat: 6-8 Maslak İstanbul  <a href="mailto:riconturkiye@riconmobile.com">riconturkiye@riconmobile.com</a> +90 212 346 26 00	<b>Ricon Turkey Office ITU</b> Reşitpaşa Mah. ITU ARI 3 Teknokent No:4-Z101 Sarıyer İstanbul  <a href="mailto:riconturkiye@riconmobile.com">riconturkiye@riconmobile.com</a> +90 212 346 26 00	<b>Ricon Italy Office</b> Via Tiziano Nr. 32 20145 Milano Italy  <a href="mailto:riconitaly@riconmobile.com">riconitaly@riconmobile.com</a> +39 347 423 3225
--	---	--	--