

Ricon

S9922M44-LTE

Industrial Router
Datasheet



Efficiency Through Innovative Technology

S9922M44-LTE Industrial Router



RICON S9922M44 Router by Ricon Mobile Inc. Industrial grade quality, designed and manufactured in accordance with 3G/LTE cellular network technology. With embedded cellular module, ATM connection, remote office security connection, data collection etc. It is widely used in many cases such as.

Ricon Mobile S9922M44 router provides maximum service to customers while Zero touch-SMS installation minimizes the need for field service with easy and automatic product installation service. S9922M44 Router, Single Module Single SIM hardware type. The best throughput value of the S9922M44 Router is 200 Mbps.

Mobile S9922M44 routers are web-based and easily routed through CLI. In addition, the Ricon Management System (RMS) successfully accomplishes the goal of reducing the maintenance costs with the ability to access all the Ricon products in the network and to access instant and statistical data on the web environment and manage them 100%.

S9922M44-LTE Models & Quick Specifications



S9922M44-LTE



- 4 x 10/100TBase Ethernet LAN Interface
- 1 x 10/100TBase Ethernet WAN Interface
- 2 x SIM Slots (Passive Backup)
- Single GSM Module
- (4.5G)LTE+/LTE/DC-HSPA+/HSPA+/HSPA/(3G)WCDMA/2G
- WEB UI/CLI/SNMP/Telnet/SSH
- Ricon Management System (RMS)
- Component-level Industrial Design
- 2x2 LTE MIMO SMA Antenna
- 802.11b/g/n Wi-Fi

S9922M44-LTE Router Specifications

Interfaces



- » 4 x 10/100BaseT LAN Interface (MDI-X)
- » 1 x 10/100BaseT WAN Interface
- » 2 x SMA-K antenna connector (MIMO)
- » 2 x Standard SIM/R-UIM Interface
- » 1 x Reset Switch
- » 1 x WPS Switch
- » 1 x DC Power socket

Indicators



- » 3G/4G1 : RF Indicator
- » 3G/4G2 : RF Indicator
- » SIG1 : GSM Module 1 Signal Attachment
- » SIG2 : GSM Module 2 Signal Attachment
- » DATA : Connection Establishment
- » RUN : System O/S Health
- » WLAN : Wireless LAN Connection
- » WAN : Wide Area Network Cable Connection Status
- » LAN : Local Area Cable Connection Status (Lan1~Lan4)

Power



- » On Idle: 80mA + 12VDC
- » Single Module Power Consumption : <5W
- » Power Feed : 5 - 35VDC

Physical Specs



- » Dimensions : 178mm x 105mm x 28mm (except antenna)
- » Weight : 464 gr.
- » Industrial Alloy Metal Housing

Specifications

S9922M44-LTE Industrial Router

Cellular Networks



- » EDGE/GPRS
- » FDD-LTE/TDD-(4.5G)LTE
- » (3G)WCDMA/UMTS/HSPA/HSPA+ CDMA2000 EVDO/CDMA 1x
- » Ethernet Standard
- » IEEE 802.3
- » IEEE 802.3U

Wi-Fi



- » Standard: IEEE 802.11b/g/n
- » AP, Client, Station, Bridge Mode Support
- » WEP, WPA and WPA2 encryption w/AES-TKIP
- » IEEE 802.11ac Optional 5Ghz Wi-Fi support
- » SSID Isolation Support
- » Channel manipulation support
- » 20Mhz/40Mhz beamer support
- » Dual Mesh Radio Application with 802.11ac

Temperature Recognition

- » Operation Temp.: -20°C to +70°C
- » Store Temp: -40°C ~ +85°C
- » Related humidity: <95 (noncondensing)

VPN

- » IPSec
- » PPTP/L2TP client
- » GRE/IPIP
- » OpenVPN

Device Management

- » Local or remote web browser (IE v8 or above)
- » CLI/Telnet command
- » RMS Ricon Management System (optional)
- » SSH config (optional)
- » Standard: IEEE 802.11b/g/n/ac optional)
- » AP, Client, station, bridge mode support
- » WEP, WPA and WPA2 encryption

Multiple Links Connection Insurance

- » Dual SIM single module for cold backup
- » Dual SIM dual module for hot backup or for load balance
- » SIM/WAN backup, dual SIM backup
- » WAN/SIM1/SIM2, links backup

Firewall & Filtering

- » IP packet/Domain/MAC Filter
- » NAT
- » DMZ

Feature

- » Support OpenWrt
- » Support feature customize with API
- » CPU: 580MHz
- » SDRAM: DDR2 256 MB
- » Flash: 128Mb

Certifications



Health	EN 62311
Safety	EN 60950 - 1+A11+A1+A12
EMC	EN 301-489-1/-7/-17/-24
	EN 55022, EN 55024
Radio	EN 301 511
	EN 301 908-1/-2
	EN 300 328



S9922M44-LTE Industrial Router

Routing Protocols

- » Statik route
- » RIPv2 / OSPF dynamic route
- » VRRP

Multiple Working Modes

- » LED monitor
- » Internal Storage
- » Support WEB, CLI, SSH, multiple parameter management
- » Data trigger online/offline
- » LCP/ICMP/flow/heartbeat check, ensure network usability

Ultra Secure Data Transmission

- » VPN support GRE/L2TP/PPTP/IPSec/OpenVPN
- » GRE over IPSec, IPSec over PPTP/L2TP
- » Supports DHCP Server
- » SNMP network management, NTP support, GPS clock support
- » OSPF, RIP, BGP optional
- » Optional QoS (Quality of Service) smart control base on protocol, application,IP subnet

Easy Maintenance Operation

- » Support local /remote firmware and patch upgrade
- » Support parameter backup and import, Support encryption
- » Support CFE firmware upgrade (Never about crash when doing upgrade)
- » Support Console port maintenance
- » Support smart switch when using multiple server
- » Local/Remote log for easy debugn

Full Network Mode

- » 4G(TD-LTE/FDD LTE), DS-HSPA+, HSPA+, HSPA, WCDMA, EVDO, TD-SCDM, CDMA1x , EDGE/GPRS
- » WAN, WLAN, SIM1\SIM2 multiple way network
- » WLAN AP/station/repeater, 802.11n(802.11ac optional), at most 300Mbps
- » 4 LAN port
- » WAN support ADSL(PPPoE), static IP, DHCP client
- » Support VPDN, APN private network
- » 802.11b/g/n(ac optional) Wi-Fi optional, WPS key
- » Supports DNS proxy and Dynamic DNS (DDNS)

RMS Ricon Management System

- » Great monitor capability
- » Remote terminal management maintenance
- » Check status of internet at any time
- » GIS showing device location
- » Debug remotely
- » Flow static and analyze

EMC4 Industrial Design, Stable and Durable

- » Aluminum shell, IP30 protection
- » System security isolation, Particularly suitable for the application of industrial control field
- » Wide range power supply (DC 5-35V)
- » Support WDT
- » Antenna lightning protection
- » SIM/UIM port: 15KV ESD protection
- » Power port: reverse-voltage and overvoltage protection
- » Ethernet port: 1.5KV magnetic isolation protection

CONTACT

RICON GLOBAL OFFICES

RICON MOBILE INC. (HQ)
460 Brant Street
Unit 300
Burlington, Ontario
Canada L7R4B6
Phone: 289-288-4110

RICON MOBILE INC. , LTD.
F5-Building 3,
FengMenAo Industrial Park,
Bantian Streets, Longgang District
Shenzen, 51829, China

RICON MOBILE INC.
Ahi Evran Cad. No:21,
Polaris Plaza Kat:8/40
Maslak / Istanbul / Türkiye
Phone: +90-212-346-2600

RICON MOBILE INC. FZE
Ras Al Khaimah U.A.E.
Phone: +97-172-041-010