

# Ricon Mobile S9960ME



## L2/L3 SFP Router Switch Datasheet

Efficiency with Innovative Technology


## S9960ME L2/L3 SFP Router Switch




The **RICON S9960ME SFP Router Switch** is a mobile network router designed based on Fiber, WiFi and VPN technologies. It is equipped with a powerful 64-bit processor and an operating system specially developed by Ricon Mobile. It can easily connect any network device connected via interface connections such as Ethernet and WiFi to the Internet or a central local network with a simple configuration.

S9960ME SFP Router Switch; It is a fiber optic terminator switch that allows the distribution of fiber lines to companies or end users via Ethernet.

### S9960ME SFP Router Switch Models & Specifications



#### S9960ME



- 4 LAN (Gigabit)
- 1 EWAN (Gigabit)
- 1 SFP (Gigabit-Longrange)
- 1 USB 2.0
- WEB User Interface / CLI / SNMP / Telnet / SSH
- 2x2 LTE MIMO SMA Antenna
- 802.11b/g/n 2.4GHz Wi-Fi. 802.11ac 5GHz Wi-Fi (Optional)
- 1 x 802.11b/g/n Antenna, 1 x 802.11ac Antenna (Optional)

### S9960ME SFP Router Switch Device Features

#### Indicators

- » SFP :Status Indicator
- » NET :Connection Setup
- » WAN :Wide Area Network Cable Connection Status
- » LAN :Local Area Cable Connection Status (Lan1 ~ Lan4)
- » POWER :Power Status
- » VPN :Connection Status Indicator

#### Wi-Fi

- » IEEE 802.11b/g/n (2.4GHz)
- » IEEE 802.11ac optional 5GHz Wi-Fi support
- » AP, client, bridge mode support
- » WEP, WPA and WPA2 encryption with AES-TKIP
- » SSID Insulation support
- » Channel management support
- » 20MHz / 40MHz Beamer

#### Interfaces

- » LAN :4x10 /100/1000 Mbps
- » EWAN :1x10 /100/1000 Mbps
- » SFP WAN :1x10 / 100/1000 Mbps
- » DC Power Input Port :1
- » USB 2.0 :1

#### Power Specifications

- » Idle :12VDC/1A
- » Single Module Power Consumption :<5W
- » Power Supply :9-24VDC

## S9960ME L2/L3 SFP Router Switch

### Environment Parameters

- » Operating Temperature :0 °C - 40 °C
- » Dimension :240mm x 150mm x 35mm
- » Weight :392gr.

### VPN

- » IPsec
- » PPTP server/client
- » L2TP server/client
- » GRE L3

### Device Management

- » CLI
- » Telnet
- » SSH
- » Web interface
- » Ricon Management Controller
- » SNMP

### Firewall and Filtering

- » IP packet / Domain / MAC Filter
- » NAT/NAPT
- » DMZ
- » Protocol/Port Filter ACL
- » VLAN Tagging

### Routing Protocols

- » Static routing
- » RIPv2
- » OSPF
- » BGP
- » Policy based Routing

### Data Features

- » QoS
- » IPv4/IPv6, TCP/IP, UDP, RTP, SNTP, DNS, DDNS
- » DHCP Server/Client/Forwarding(Relay)
- » DHCP Static MAC

### Maintenance Operation

- » Firmware update support
- » Configuration backup, ability to restore
- » Automatic firmware update
- » Local/remote systems logging

### Network Mode

- » WAN
- » WLAN
- » WIFI
- » 802.11n 2.4 GHz, 802.11b/g/n/ac 5.8 GHz optional Wi-Fi
- » PPPoE support
- » WPS support
- » DNS proxy ve Dinamik DNS (DDNS) support

### Certifications

» Health	EN 62311
» Safety	EN 60950 - 1+A11+A1+A12
» EMC	EN 301-489-1/-7/-17/-24
	EN 55022, EN 55024
» Radio	EN 301 511
	EN 301 908-1/-2
	EN 300 328



# CONTACT

## RICON GLOBAL OFFICES

### RICON MOBILE INC. (HQ)

1100 Burloak Drive,  
Suite 300  
Burlington, Ontario  
L7L 6B2  
riconrequest@riconmobile.com  
Phone: +1 905 921 31 22

### RICON ITALY

Via Tiziano Nr. 32 20145 Milano (MI)  
ITALY  
www.riconmobile.com/it  
riconitaly@riconmobile.com  
Phone: +39 335 5444061



### RICON MOBILE INC.

Resitpasa Mah. ITU ARI 3 Teknokent  
No:4- Z101  
Maslak / Istanbul / Türkiye  
Phone: +90-212-346-2600